

AND FIRE RATED
PFT™ DOOR FRAMES



20 MINUTE FIRE RATED DOORS

Fire, one of the four elements is an important part of our world. However, its flames have the potential to cause severe physical damage. Fires not only have a negative impact on the environment, they also impact the lives of people and their property. It is essential to have the best and safest products to protect you and your loved ones around this element.

To minimize the severity of a fire, our Plastpro Fire Rated Doors are extremely durable. Made with fire-resistant composite, our doors are tested and comply with safety and performance standards to withstand fire for a minimum of 20 minutes. Our doors add extra protection to your home without ever sacrificing style.

1 EXTENDED LOCKBLOCK

The full length LVL increases the rigidity of the door.

2 FIRE RETARDANT COMPOSITE

Our HFO Polyurethane fire rated foam system is specially formulated to withstand fire.

3 FULL LENGTH COMPOSITE STILES

Our full-length composite stiles protect the door from external exposure.

4 PLASTPRO® EXCLUSIVE SMC SKIN

Our skin material is specially formulated and comes in various panel configurations.

5 COMPOSITE BOTTOM RAIL

High strength rails prevent moisture from seeping into the door.



Intertek
CERTIFIED



ENERGY STAR
PARTNER

TESTING RESULTS

Our 20 minute Fire Rated doors are tested for single swing fiberglass doors. Tests are done to multiple standards and bear the Warnock Hersey Mark of product safety, performance, and quality.

ULC 10 C / NFPA 252 / ASTM E 2074 | FIRE RATED CSFM 12-7A-1 | EXTERIOR WILDFIRE EXPOSURE TEST

- 6'8" Doors are tested with Wood, Steel & 20 min Fire Rated PF™ Door Frame
- 7'0" Doors are tested with Wood & 20 min Fire Rated PF™ Door Frame
- 8'0" Doors are tested with Wood & 20 min Fire Rated PF™ Door Frame
- All Doors are tested for single units only



CRAFTSMAN SERIES

20 MINUTE FIRE RATED DOORS

6'8"

2'8" • 3'0"



DRS1K

8'0"

3'0"



DRS1K80

6'8"

2'8" • 3'0"



DRS2K

8'0"

3'0"



DRS2K80

6'8"

2'8" • 3'0"



DRS3F

6'8"

2'8" • 3'0"





DRS50



SMOOTH SERIES

20 MINUTE FIRE RATED DOORS

<p>6'8"</p>  <p>2'8" • 3'0"</p>	<p>7'0"</p>  <p>3'0"</p>	<p>8'0"</p>  <p>3'0"</p>	<p>6'8"</p>  <p>2'8" • 3'0"</p>
<p>DRS500</p>	<p>DRS0070</p>	<p>DRS0080</p>	<p>DRS2B</p>
<p>6'8"</p>  <p>2'8" • 3'0"</p>	<p>8'0"</p>  <p>3'0"</p>	<p>6'8"</p>  <p>2'8" • 3'0"</p>	<p>8'0"</p>  <p>3'0"</p>
<p>DRS2D</p>	<p>DRS2D80</p>	<p>DRS2G</p>	<p>DRS2G80</p>

20 MINUTE FIRE RATED DOORS



DRS22



DRS2270



DRS2280



DRS29



DRS41



DRS4170



DRS60



DRS61



DRS6170



DRS63

RUSTIC SERIES

6'8"



3'0"

DRA2A



OAK SERIES

6'8"



3'0"

DRG60



20 MINUTE FIRE RATED DOORS

PFT™ DOOR JAMBS

Our exclusive PFT™ Door Jambs add needed protection for your entry units. Also made with fire retardant composite, Plastpro Poly-Fiber Jambs are tested and certified to withstand fire for 20 minutes. Complete your protection by fitting your fiberglass door with PFT™ Door Jambs.



FEATURES & BENEFITS

- Equipped with HydroShield technology, it will not absorb or wick moisture, and prevents warping, rotting, and splitting.
- Frame is not able to be infested with termites at any point along the structure.
- More versatility in design. Available in various lengths and widths that can be stained as well as painted.
- Has twice the screw holding power of traditional wood door frames.

FRAME DECAY COMPARISON



PLASTPRO PFT™ DOOR JAMB

*with Hydroshield Technology™



TRADITIONAL WOOD FRAME

Susceptible to rotting, warping and decay

TESTING RESULTS

ULC 10 C / NFPA 252 / ASTM E 2074 | FIRE RATED
CSFM 12-7A-1 | EXTERIOR WILDFIRE EXPOSURE TEST

- All PFT™ Door Jamb are tested for single swing units only.



GRAIN STYLES



• OAK GRAIN



• FIR GRAIN



• MAHOGANY



• PRIMED



• WHITE CAPPED

PFT™ DOOR JAMBS



www.plastproinc.com

5200 W. Century Blvd, 9th Floor ■ Los Angeles, CA 90045

Phone: (800) 779-0561 ■ Fax: (310) 693-8620



© 2024 Plastpro Inc. All Rights Reserved

Product # MKLFRB2024 Updated March 2024